



Kinco's new gen industrial HMI

GREEN Series 2nd Gen. Industrial HMI G2156E

Product features

- 15.6" display with 2K resolution and 16 million true colors;
- Single Ethernet port and dual serial port design, reliable communication;
- Quad-core CPU with 512MB RAM and 4GB flash storage, ultimate performance;
- Metal shell with power isolation, safe and reliable;
- Comes with the latest Kinco DToolsPro configuration software.

Kinco new generation configuration software : **Kinco DToolsPro**

Office-style interface with a fresh and modern look

Tag variable configuration mode that is closer to ST language programming habits

Template configuration for a more efficient development experience



Kinco's new
gen industrial HMI
GREEN Series
2nd Gen. Industrial HMI
G2156E



Model	G2156E
Performance specifications	
Display size	15.6" TFT
Display area	344.16(W)x193.59(H)
Resolution	1920*1080 pixel
Display color	16.7M
Display viewing angle	80/80/80/80(left/right/up/down)
Contrast ratio	1000:1
Backlight	LED
Brightness	250cd/m2
Backlight life	>20000hours
Touch panel	4 line precision resistance network(surface hardness 3H)
CPU	Quad-core ARM 1.5GHz
Memory	4GB NAND Flash Memory+512MB RAM
RTC	Built-in
Extensible memory	1 USB Host
Print port	USB Host/serial port
Ethernet	LAN0:10/100 Mbps
Program download	Ethernet port/USB Slave/U disk
Com port	COM0:RS232/RS485/RS422; COM2:RS232;
Electrical specifications	
Input power supply	DC18V~DC28V,built-in isolated power supply
Rated power	15W@DC24V
Insulation resistance	Over 50MΩ@500V DC
Pressure resitance test	500 VAC 1 minute
Structure specifications	
PCB	Built-in
Shell material	Metal
Overall dimension	395x259x25.5mm
Cut-out dimension	381.5x245.5mm
Installation mode	Installation of Fasteners and VESA Mounting(VESA100 *100mm)
Weight (kg)	2.5KG
Environmental specifications	
Working temperature	0~50℃
Working Humidity	10~90%RH (Non-condensing)
Storage temperature	-20~60℃
Storage humidity	10~90%RH (Non-condensing)
Seismic resistance	10~500Hz,30m/s²,X,Y,Z direction/hour
Cooling mode	Natural air cooling
Product certification	
Panel protection grade	IP65 certification(4208—93)
CE authentication	EN61000-6-4:2019, EN61000-6-2:2019)
Software	
Configuration software	Kinco DToolsPro

Dimensional diagram (Unit: mm)

